

Improvements and bugfixes:

- Implementation of three new FM RDS settings to optimize FM-reception – selectable in the System > Setup > General > NoiseMasking
The following selections are available: “Standard”; “Mono”; “Music”
The chosen new FM sub-set only becomes effective upon device restart over ignition.
- Integration of a new OSD system language (Hungarian)
- Improved default setting: internal BT microphone selected ex-factor, AF function turned on ex-factory
- Additional improvements and system code alignments

Requirements:

- USB memory stick of at least 4 GB data size.
Note: The USB stick must be formatted to FAT32 before use (right-click on the USB drive in the Windows Explorer → choose “Format” → select FAT 32 → start).
- A Windows OS based PC or notebook to prepare the USB memory stick.

Installation of the software update:

1. Download the software update package „ZE-NC5011D__ELS_Update_V0613.zip”.
2. Unzip the software update package to you USB stick.
3. You obtain a folder „C9D_SW_Update“ appearing in the root directory of the USB stick.
4. Connect the USB memory stick to your naviceiver.
5. Enter the naviceiver setup menu. Tap on “MISC” → “Update” → Software “OK”.
6. The naviceiver will restart and show an update dialog menu.
7. Make sure, checkboxes „1.App“ and „6.MCU“ are selected. Tap on the „Update“ button to start the update process.
8. Your system will be updated in a sequential process. The complete update procedure takes approx. 3 minutes. A status bar shows the update progress.
9. The device will restart automatically once the update process has completed successfully.
10. Calibrate the touch screen with a suitable pen.
11. Remove the USB memory stick.

Version checking:

After completion of the software update, version checking is crucial to validate full success. If the installed software version differs with versions listed below, a full re-installation of the entire software update package is due.

Review of device software version:

To check the versions of Application and MCU, enter the naviceiver setup menu. Tap on “MISC” → „Info“ → Show Info Software „OK“

MCU: 0.2.0_03H3_130515

APP: 3.2.02_03H3_130530

(Only the version numbers shown above are relevant)